



AFA&COLOUR 2K ROAD PAINT

DESCRIPTION

:AFA COLOUR 2K ACRYLIC PAINT is based acrylic resin, double component and cold application paving asphalt paint.

FEATURES AND SCOPE OF USAGE

:It is single colour paint with two components which contains resin and makes chemical drying with its polyisocyanate resin hardener and has high physical and chemical resistance. The film thickness at the surface can be adjusted between 1 mm and 5 mm. Thanks to its high strength, it can keep its substantivity for a long period of time. It consists of AFA COLOUR 2K Akrilik Hardener and Acrylic Thinner.

MIXTURE(BY VOLUME)

:Product 2 part
Hardener 1-2%
Thinner 7-10%

APPLICATION

:The surfaces of application should never be damp, and should be thoroughly cleaned up of dirt, grease, old and swollen paints. Drying occurs by the chemical reaction taking place by blending powdery hardener to liquid road marking paint by the ratio of 1 – 2%. Therefore, application must be initiated within maximum 5-7 minutes after the hardener has been blended.

CAUTIONS FOR DANGER AND SECURITY:

- S2** Keep away from children.
- S 24/25** Avoid eye and skin contact.
- S 3/7/9** Keep it in a tightly closed container.
- S 16** Keep away from flammable source, do not smoke.
- S 51** Good aspiration conditions
- R 20/21/22** Aspiration, skin touch and swallow are dangerous.
- R 10** Flammable

STORAGE

:Containers tightly closed must be protected from frost keep in a cool sheltered place Best before: 1 year.

PACKING

: 25 KG(A+B COMPONENT)

***Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**