



AFA & COLOUR ANTIBACTERIAL PLASTIC WALL PAINT

DESCRIPTION	:Acrylic based , antibacterial, matte, interior flat top coat emulsion paint.
FEATURES AND SCOPE OF USAGE	:It is applied with a normal or rolling brush on the internal surfaces, timber, concrete, bricks, on-plaster, ytong, hardboard and similar construction materials.
APPLICATION	:The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, grease and swollen paints and be readied for last coating with AFA BINDER PRIMER PAINT. Its adhesion, flexibility and resistance to water and alkalines are excellent. depending on the darkness of the surface color. It ensures respiration between surface and wall. Temperature for application is between +5°C and +30°C for surface. Recoatable: 6 hours.
CAUTIONS FOR DANGER AND SECURITY	: S2 Keep away from children. S 24/25 Avoid eye and skin contact. S 3/7/9 Keep it in a tightly closed container.
STORAGE	:Containers tightly closed must be protected from frost keep in a cool sheltred place. Best before: 1 year
TECHNICAL SPECIFICATIONS	:PH: 8-9 Brightness: 2-4 Gloss (20°) Viscosity:138-140 KU
APPLICATION TIME	:Apply it at a temperature of over +5 °C. Coating capacity (liter): 10-12 m2/lt
PERCENTAGE OF SOLID MATERIAL	:70% , (for 20 °C) Sanding time: 15 minutes, Touch-dry in 45 minutes,
CHEMICAL DRYING	:24-72 hours.
PACKAGE	:20 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**