



AFA & COLOUR CASHMERE WALL PAINT WITH SILICONE

DESCRIPTION	:Acrylic and silicon-treated water-based matt last coating paint.
FEATURES AND SCOPE OF USAGE	:It is applied with a normal or rolling brush on the internal surfaces, timber, concrete, bricks, on-plaster, ytong, hardboard, ceiling and similar construction materials. Depending on the application, Water-thinnable, harmless to environment, perfect adhesion, vapor permeable, fast drying, scrub resistant, perfect working properties.
APPLICATION	:The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, grease and swollen paints and be readied for last coating with AFA BINDER PRIMER PAINT. Its adhesion, flexibility and resistance to water and alkalines are excellent. depending on the darkness of the surface color. It resembles satin with its semi matte outlook, and its effaceability is incomparably higher than other plastic paints. It ensures respiration between surface and wall. Temperature for application is between +5°C and +30°C for surface. Recoatable: 6 hours.
CAUTIONS FOR DANGER AND SECURITY	: S2 Keep away from children. S 24/25 Avoid eye and skin contact. S 3/7/9 Keep it in a tightly closed container.
STORAGE	:Containers tightly closed must be protected from frost keep in a cool sheltred place. Best before 1 year.
PACKAGE	:20 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**