



## AFA & COLOUR EPOXY TOPCOAT PAINT

|   |   |
|---|---|
| <b>DEFINITION</b>                       | : A synthetic epoxy polyamide resin based, two component and epoxy Top coat paints against chemical and physical effects.   |
| <b>COLOURS</b>                          | : All colours in the AFA Industrial Paints catalogue are available on order.  |
| <b>GLOSSINESS</b>                       | : Glossy.   |
| <b>SOLIDS</b>                           | : Depending upon the colour, 50-60 % (Including the hardener)   |
| <b>SPECIFIC GRAVITY</b>                 | : Depending upon the colour, 1.10-1.32 gr/cc  |
| <b>MIXTURE</b>                          | : 2 Parts of paint should be added to 0,6 part of hardener in terms of weight, and mixed thoroughly. This mixture should be consumed within 14-16 hours as it has a life span of about 14-16 hours and starts to jellify at the end of the said period.   |
| <b>THINNER</b>                          | : AFA Epoxy Topcoat should only be thinned by using its special thinner, AFA Epoxy Thinner.   |
| <b>DRYING PERIOD</b>                    | : At 20°C, AFA Epoxy Topcoat completes its surface drying in 1.5-2 hours and becomes dry to the touch in 20-22 hours. The complete ossification period rendering the paint resistant against chemical effects is 6-7 days after application. In order to accelerate drying and ossification, the surface could be oven dried for 1 hour at 80°C |
| <b>APPLICATION</b>                      | : 2 Parts of paint should be added to 0,6 part of hardener in terms of weight, and mixed thoroughly. This mixture should be consumed within 14-16 hours as it has a life span of about 14-16 hours and starts to jellify at the end of the said period.   |
| <b>CAUTIONS FOR DANGER AND SECURITY</b> | : <b>S2</b> Keep away from children.<br>: <b>S 24/25</b> Avoid eye and skin contact.<br>: <b>S 3/7/9</b> Keep it in a tightly closed container.<br>: <b>S 16</b> Keep away from flammable source, do not smoke.<br>: <b>S 51</b> Good aspiration conditions<br>: <b>R 20/21/22</b> Aspiration, skin touch and swallow are dangerous.            |
| <b>STORAGE</b>                          | : Containers tightly closed must be protected from frost keep in a cool sheltered place Best before: 1 year.  |

\*Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.