

EPOXY VARNISH

DESCRIPTION

FEATURES and SCOPE of USAGE

APPLICATION

CAUTIONS FOR DANGER AND SECURITY

STORAGE

:It is a combination of Epoxy resin and Polyamide hardeners, diffuse to concrete well, epoxy surface varnish.

:It is used to vovering epoxy surfaces prior to purpose of impregnation. It covers and filled the cracks.It acts as adhesive between applied floor surface and next coat. It is applied by itself to obtain transparent floor cover coat.

:Concrete surfaces should be clean well.Bright surfaces can roughed by frez. Apply dust free, dry and clean urfaces two coat wait one day between the coats. No need to use thinner.Apply with brush, roller and spray. Apply finish coat next day.Use Aksan Epoxy Thinner to clean the equipment.

:S2 Keep away from children.

S 24/25 Avoid eye and skin contact.

S 3/7/9 Keep it in a tightly closed container.

S 16 Keep away from flammable source, do not smoke.

S 51 Good aspriation condinations

R 20/21/22 Aspiration, skin touch and swallow are dangerous. :Containers tightly closed must be protected from frost keep in a cool sheltred place Best before: 1 year.

^{*}Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.