



AFA COLOUR TRANSFORMATION PRIMER

DESCRIPTION	:Acrylic copolymer emulsion-based interior primer.
FEATURES AND SCOPE OF USAGE	:Forms a binding bridge between the paint and the surface. It is used as a primer on brute concrete, smooth and rough plasters, mineral-based surfaces, and faded self-supporting silicone or acrylic-based old painted surfaces.
APPLICATION	:Ensure the application surface is smooth, secure and in a well condition to hold the primer and the top-coat paint.Recommended to be applied in two coats after thinning by 10% with clean water in brush and roller applications. Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 5% with clean water in airless spraying. Apply as a single coat using a brush or roller. AFA COLOUR BOYA Interior Transformation Primer drying time is 6 hours when applied on water-based paint and 24 hours when applied on solvent-based paint (drying time can increase at higher relative humidity and lower temperature values).
CAUTIONS FOR DANGER AND SECURITY	: S2 Keep away from children. S 24/25 Avoid eye and skin contact. S 3/7/9 Keep it in a tightly closed container. Xi Irritating. H317 May cause sensitization by skin contact.
STORAGE	:Containers tightly closed must be protected from frost keep in a cool sheltred place. Best before1 year.
PACKAGE	:20 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**