



## AFA&COLOUR HAMMERTON PAINT

### DEFINITION

:It is a alkid based high colour paint ; that can dry in an open area very quickly an that gives a hammer effect. Appearance to the metal surfaces it is applied and that has a high relining and elasticity capacity.

### APPLICATION

:It is used over office materials, tables, steel wardrobe, shelves chairs, machines, electrical equipment.

### COLOUR

: Colours are available according to orders.

### BRIGHTNESS

: Glossy.

### THINNING

: It should be thinned with Unlu Rapid Hammerton Thinner.

### APPLICATION WITH

: It is applied with pistol.

### TOUCHING DRYING

: 20-30 minutes.

### AREA THAT CAN BE PAINTED

: An area of 10-12 m<sup>2</sup> can be painted with .( It AFA Hammerton paint, according to dry film thickness).

### APPLICATION

: Dust, filth and oil should be removed completely from the surface to be painted.It should be applied at 20°C /DIN CUP with interval of 4/25-28 seconds.It should reach the proper viscosity with AFA Rapid Hammerton Thinner and applied at low pressure from proper distance.Pattern formation can be adjusted by thinning and compressor pressure.During the application period the paint should be regularly stirred.

### CAUTIONS FOR DANGER AND SECURITY

: **S2** Keep away from children.

**S24/25** Avoid eye and skin contact.

**S3/7/9** Keep it in a tightly closed container.

**S16** Keep away from flammable source, do not smoke.

**S51** Good aspiration condinations.

**R20/21/22** Aspiration, skin touch and swallow are dangerous.

### STORAGE

: Containers tightly closed must be protected from keep in a cool sheltred place Best before : 1 year

**\*Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**