



AFA COLOUR METALLIC WALL COATING PAINT (S100)

DESCRIPTION

:Acrylic copolymer emulsion based,gloss,thick grained metallic decorative paint can be used on interior and exterior surfaces.

FEATURES AND SCOPE OF USAGE

:It is water based and integrates with applied surfaces. It is not done cracking, swelling and spalling. All kinds of surfaces of the structural elements necessary adjustment should be made before applying.

APPLICATION

:Surfaces to be administered certainly not damp,oil,dirt,dust and Completely should be cleaned before applying. The surface should be painted and prepared using for interior AFA COLOUR SILICONE PLASTIC WALL PAINTS and for exterior AFA COLOUR SILICONE TEXTURE COATING. For interior walls;paint applied with the desired patterned rolls, Sponge etc. are applied to the directly without dilution with Decorative tools,for exterior walls; threaded paint applied with the desired patterned rolls without dilution. Application should be Done very quickly. During the application should not be attempted indirect sunlight or wind environment. If the containers tap is opened as a result of exposure to air dries product, so the product Must be consumed immediately.

CAUTIONS FOR DANGER AND SECURITY

:S2 Keep away from children .

S 24/25 Avoid eye and skin contact .

S 3/7/9 Keep it in a tightly closed container

TECNICAL SPECIFICATION

PH

:8-9

Density

:1,1 – 1,15 gr/cm3

Aplication Time

:Apply it a temparature of over +5 C

Coating Capasity

:Depends on the thichness of 1 kg with 4 m2 covered

Percentange of solid material

: % 50

Dust drying

: 20-30 minutes

Touch Dry

:1-2 hours

Chemical Drying

:48 hours.

STORAGE

:Containers tightly closed must be protected from frost.Keep in a cool sheltered placed the shelf life when stored in the specified conditions is 1(one) month

*Please consult our technical service department for details which are not sufficient the technical specifications.