



AFA COLOUR METALLIC WALL COATING PAINT (S300) THICK

DESCRIPTION

:Acrylic copolymer emulsion based,gloss,thick grained. Metallic decorative paint can be used on interior and exterior surfaces..

FEATURES AND SCOPE OF USAGE

:It is water based and integrates with applied surfaces. It is not prone to cracking, swelling and spalling. All kinds of surfaces of the structural elements like concrete plastered and painted surfaces, gypsum and gypsum board, wood etc, necessary adjustments should be made before applying. A very hard surface is obtained.

APPLICATION

:Surfaces to be administered certainly not damp, oil, dirt, dust and completely cleaned of old paint should be ready for top coat with using AFA BINDER or AFA SILICONE EXTERIOR PRIMER, by applying to surface with POLYPUTTY EXTERIOR PASTE. First floor without diluting First floor without diluting AFA COLOUR METALLIC WALL COVERING S300 THICK is applied and is given the desired pattern without waiting patterned roll. The finish and patterned roller application should be implemented quickly. During the application should not be attempted in direct sunlight or wind environment. If the containers tap is opened as a result of exposure to air dries Product, so the product must be consumed immediately.

CAUTIONS FOR DANGER AND SECURITY:

S2 Keep away from children .

S 24/25 Avoid eye and skin contact .

S 3/7/9 Keep it in a tightly closed container

TECNICAL SPECIFICATION

PH

:8-9

Density

:1,50 – 1,55 gr/cm3

Aplication Time

:Apply it at a temperature of over +5 C

Coating Capacity

:Depends on the thickness of 1 kg with 0.75-1 m2 covered

Percentage of solid material

:% 70

Dust drying

:1-2 hours

Touch Dry

:5-6 hours

Chemical Drying

:48 hours.

STORAGE

:Containers tightly closed must be protected from frost. Keep in a cool, sheltered place. The shelf life when stored in the specified conditions is 1 month.

*Please consult our technical service department for details which are not sufficient the technical specifications.