



AFA&COLOUR POLIPASTE S100

DESCRIPTION

:Cement Based, 2 Components Adhesive Mortar of high quality. It includes special chemicals, additives prepared specially with the cement of high quality. It is water proofing, very flexible and thermal mortar to use as a putty any strong surfaces.

WHERE TO USE

:Cremic adhesive Mortar
Granite adhesive Mortar
Gas Concrete adhesive Mortar
Flex Granite adhesive Mortar
EPS and XPS adhesive Mortar (Polystyrene Head Board)
Pool and Wet Floor adhesive Mortar
Concrete, plaster, glass and aluminium
Water tanks

TECHNICAL FEATURES

:Appearance: Grey colored powder and Emulsion solution
Application Temperature: +5°C/+35°C
Pot Life : 1,5-2 hours
Open time : 20 minutes

APPLICATION PROCEDURE

:Application surface must be strong and purified from the residues (such as dirt, dust, paint etc)
20 Kg A component (Dry Mortar) is poured into
1 Kg B component (Liquid) and it is mixed with
a mixer to let the chemical reaction done, it is kept waiting for 5 minutes and mixed again for 2 minutes, before using. To thin the mixture can be done with some water. Also the B Component (Liquid) can be used as wet , volume locations (baths, terrace, balcony) can be mixed up to 60 % water.

PACKAGE

:20 Kg kraft bag

STORAGE

1 Kg can container

:Storage life is 6 months in a dry place in its original package .

***Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**