



AFA COLOUR INDUSTRIAL RAPID PAINT

DEFINITION

: Alkyd resin based, glossy finishing coat paint with very rapid surface drying

COLORS

: Colours are available according to orders

BRIGHTNESS

: Gloss, Semi gloss or Mat

SOLIDS

: Depending upon the color, 45- 60 %

SPECIFIC GRAVITY

: Depending upon the color, 1,0-1,28 g/ml (20 C)

THINNER

: Could be thinned by using AFA Industrial Rapid thinner.

DRYING

: Dust dry : 15-20 minutes

Hard Drying : 3 – 6 hours

SURFACE PREPARATION

: The dirt, oil etc, on the surface should be cleaned by using generally accepted surface preparation methods and the surface should be made suitable for painting.

APPLICATION

: Although AFA Industrial Rapid Paint could be used with or without a primer, it is recommended to apply it on a primer to obtain better results. One coat of Afa Industrial primer and then one coat of Afa Rapid Industrial Finishing Coat Paint should be applied on the cleaned surface. As it is a rapidly drying paint, the main application method is application by air spray. To obtain a much glossier and better surface, a second coat should be applied 10 – 15 minutes after the application of the first coat. AFA Industrial Rapid thinner should be used.

CAUTIONS FOR DANGER AND SECURITY

: **S2** Keep away from children.

S24/25 Avoid eye and skin contact.

S3/7/9 Keep it in a tightly closed container.

S16 Keep away from flammable source, do not smoke.

S51 Good aspiration conditions.

R20/21/22 Aspiration, skin touch and swallow are dangerous.

STORAGE

: Containers tightly closed must be protected from keep in a cool sheltered place Best before : 1 year

***Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**