



AFA&COLOUR ANTI-RUST PAINT

DESCRIPTION

:AFA&COLOUR SYNTHETIC ANTIRUST PAINT is alkyd-and solvent-based matt construction antirust paint.

FEATURES AND SCOPE OF USAGE

:It is applied with a normal or Rolling brush on internal and outer surfaces,metal,brick and similar construction materials.It is thinned by means AFA SYNTHETIC THINNER.

APPLICATION

: The surfaces of application should never be damp,and should be thoroughly cleaned up of dirt, grease,old and swollen paints, readied for painting.Its adhesion, flexibility,water-resistance, against alkalines and acids are excellent.Never apply a second coating before the first one is dried up.It reduces last coating consumption and readies the surfaces for last coating.Please, thin the paint so that the paint so that the brush can be used conveniently.Do not add excessive amounts of solvent.

CAUTIONS FOR DANGER AND SECURITY

: **S2** Keep away from children.
S24/25 Avoid eye and skin contact.
S3/7/9 Keep it in a tightly closed container.
S16 Keep away from flammable source, do not smoke.
S51 Good aspiration condinations.
R20/21/22 Aspiration, skin touch and swallow are dangerous.

STORAGE

:Containers tightly closed must be protected from keep in a cool sheltered place Best before : 1 year.

TECHNICAL SPECIFICATIONS

:Degree of flaring:39°C , Brightness:10-15 Gloss (60°), Viscosity:105-110 KU, Coating capacity(liter):6-9 m²/lt, Percentage of solid material :75%(for20°C) Touch-dry in 50-60 Minutes,Oxydation drying :10 hours.

***Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**