



AFA&COLOUR FLEX COATING WITH SILICONE

DESCRIPTION

:Acrylic copolymer emulsion based coating for exterior surfaces. Its adhesion, flexibility and resistance to water and alkalines are excellent. It is resistant to weather conditions. It gives to surface elasticity and special decorative appearance Due to thick coat it hides surface roughness and cracks.

FEATURES AND SCOPE OF USAGE

:It is applied with external surfaces, timber, concrete, bricks, wall putty, gas concrete, hardboard, ceiling and similar construction materials. It is applied by thinning with a water of 5% or never.

APPLICATION

:The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, grease and swollen paints and be readied for last coating with AFA Acrylic External Facade Primer with silicone. In roller applications, various textures could be obtained through the use of different types of rollers and the addition of varying amounts of water. Coating capacity is 0,500-1,000 kg/m² . (It is depened on design and application)

CAUTIONS FOR DANGER AND SECURITY: **S2** Keep away from children.

S 24/25 Avoid eye and skin contact

S 3/7/9 Keep it in a tightly closed container.

STORAGE

:Containers tightly closed must be protected from frost keep in a cool sheltred place.

Best before 1 year.

PACKAGE

:20 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**