



AFA&COLOUR GRAINED COATING WITH SILICONE

DESCRIPTION

:Acrylic copolymer emulsion based, high grained coating for exterior surfaces.

FEATURES and SCOPE of USAGE

:Its adhesion, flexibility and resistance to water and alkalines are excellent. It is resistant to weather conditions. It gives to surface elasticity and special decorative appearance. Due to thick coat it hides surface roughness and cracks. It is applied with external surfaces, timber, concrete, bricks, wall putty, gas concrete, hardboard, ceiling and similar construction materials.

APPLICATION

:The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, Grease and swollen paints and be readied for last coating AFA Acrylic External facade with Primer with silicone. In roller applications, various textures could be obtained through the use of different types of rollers and the addition of varying amounts of water. Coating capacity is 0,500 – 1.000 kg/m². (It is depended on desing) It is applied by thinning with a water of 5 % or never.

CAUTIONS FOR DANGER AND SECURITY

:**S2** Keep away from children.

S 24/25 Avoid eye and skin contact.

S 3/7/9 Keep it in a tightly closed container.

STORAGE

:Containers tightly closed must be protected from frost keep in a cool sheltred place.

Best before 1 year

PACKAGE

:15 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**