



## AFA & COLOUR TINSEL WALL PAINT

### DESCRIPTION

### FEATURES AND SCOPE OF USAGE

### APPLICATION

### CAUTIONS FOR DANGER AND SECURITY

### STORAGE

### TECHNICAL SPECIFICATIONS

### APPLICATION TIME

### PERCENTAGE OF SOLID MATERIAL

### CHEMICAL DRYING

### PACKAGE

:Acrylic based , silvery, interior flat top coat emulsion paint.

:It is applied with a normal or rolling brush on the internal surfaces, timber, concrete, bricks, on-plaster, ytong, hardboard and similar construction materials.

:The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, grease and swollen paints and be readied for last coating with AFA BINDER PRIMER PAINT. Its adhesion, flexibility and resistance to water and alkalines are excellent. depending on the darkness of the surface color. It ensures respiration between surface and wall. Temperature for application is between +5°C and +30°C for surface. Recoatable: 6 hours.

:**S2** Keep away from children.

**S 24/25** Avoid eye and skin contact.

**S 3/7/9** Keep it in a tightly closed container.

:Containers tightly closed must be protected from frost keep in a cool sheltered place. Best before: 1 year

:PH: 8-9 Brightness: 2-4 Gloss ( 20° )

Viscosity:138-140 KU

:Apply it at a temperature of over +5 °C. Coating capacity (liter): 10-12 m2/ltr

:70% , (for 20 °C) Sanding time: 15 minutes, Touch-dry in 45 minutes,

:24-72 hours.

:20 Kg Plastic Package

\*Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.