



AFA & COLOUR SOLVENT-FREE EPOXY COATING

DEFINITION

:Solventless epoxy polyamide resin based, two component and glossy enamel resistant against chemical and physical effects.

COLOURS

:All colours in the Solvent-Free Epoxy Coating catalogue are available on order.

GLOSSINESS

:Glossy.

SOLIDS

:Depending upon the colour, 50-60 % (Including the hardener)

SPECIFIC GRAVITY

:Depending upon the colour, 1.10-1.32 gr/cc

APPLICATION

:2 Parts of paint should be added to 0,6 part of hardener in terms of weight, and mixed thoroughly. This mixture should be consumed within 14-16 hours as it has a life span of about 14-16 hours and starts to jellify at the end of the said period.

THINNER

:Solvent-Free Epoxy Coating should only be thinned by using its Special thinner, AFA Epoxy Thinner.

DRYING PERIOD

:At 20°C, Solvent-Free Epoxy Coating completes its surface drying in 1.5-2 hours and becomes dry to the touch in 20-22 hours. The complete ossification period rendering the paint resistant against chemical effects is 6-7 days after application. In order to accelerate drying and ossification, the surface could be oven dried for 1 hour at 80°C.

AMBALAGE

1. Komponent 12 Kg
2. Komponent (Sertleştirici) 6 KG

***Please consult our technical service department for details which are not sufficient the technical specifications. Technical modifications reserved.**