AFA & COLOUR UNIVERSAL PURE ACRYLIC FLEX COATING

DESCRIPTION :Water-base, semi gloss satin paint, based on **Pure Acrylic Flex Coating** polymer emulsion for exterior and interior uses.

FEATURES AND SCOPE OF USAGE :It is applied with a normal or rolling brush on the internal surfaces, timber, concrete, bricks, on- plaster, ytong, hardboard, ceiling and similar construction materials. Depending on the application, water-thinnable, harmless to environment, perfect adhesion, vapor permeable, fast drying, scrub resistant, perfect working properties.

APPLICATION **:**The surfaces to be treated should never be damp, be thoroughly cleaned up of dirt, grease and swollen paints paints and be readied for last coating with AFA SILICONE OUTER SURFACE PRİMER, by filling cracks, large pits and uneven areas materials. Its adhesion, flexibility and resistance to water and alkalines are excellent. It can cover the dirtiness of the lower surface with one to three coatings, depending on the darkness of the surface color. It is resistant to weather conditions, It ensures respiration between surface and wall. Always apply it at a temperature of over +5 °C. Thanks to its silicone agent, it prevents the water droplets from outside from infusing into plaster.

CAUTIONS FOR DANGER AND SECURITY **:S2** Keep away from children.
S 24/25 Avoid eye and skin contact
S 3/7/9 Keep it in a tightly closed container.

STORAGE **:**Containers tightly closed must be protected from frost keep in a cool sheltred place.
Best before 1 year.

PACKAGE **:**20 Kg Plastic Package

***Please consult our technical service department for details which are not sufficient the technical specifications.**